

# Metal Package PMT

## Photon Counting Head H11890 Series



The H11890 series is a compact photon counting head consisting of a metal package photomultiplier tube along with a high speed photon counting circuit and a high-voltage power supply unit. The high voltage supply for the photomultiplier tube and the discriminator level are preset to optimum values, allowing photon counting measurement by just connecting to a PC.

Photon counting measurement data transfer, counter gate time and other necessary adjustments are controlled by commands from the PC through the USB interface.

Since the H11890 series performs linearity correction by the internal MPU, it provides excellent count linearity within a range of -10 % at  $2 \times 10^7 \text{ s}^{-1}$ .

### Product Variations

Type No.	Spectral Response	Features
H11890-110	230 nm to 700 nm	Super bialkali photocathode, high sensitivity in visible range.
H11890-210	230 nm to 700 nm	Ultra bialkali photocathode, high sensitivity in visible range.
H11890-01	230 nm to 870 nm	Multialkali photocathode, for UV to near IR range.

This product can't be used at vacuum environment or reduced pressure environment.

### Specifications

(at +25 °C)



Parameter		H11890-110	H11890-210	H11890-01	Unit
Input Voltage		USB Bus Power			—
Max. Input Current		50			mA
Effective Area		$\phi 8$			mm
Peak Sensitivity Wavelength		400			nm
Spectral Response Range		230 to 700	230 to 700	230 to 870	nm
Count Sensitivity	Typ.	300 nm	$3.7 \times 10^5$	$3.9 \times 10^5$	$2.7 \times 10^5$
		400 nm	$4.9 \times 10^5$	$6.1 \times 10^5$	$3.6 \times 10^5$
		500 nm	$3.7 \times 10^5$	$4.6 \times 10^5$	$2.8 \times 10^5$
		600 nm	$1.1 \times 10^5$	$1.3 \times 10^5$	$2.0 \times 10^5$
		700 nm	$7.7 \times 10^3$	$9.1 \times 10^3$	$1.2 \times 10^5$
		800 nm	—	—	$3.0 \times 10^4$
Count Linearity <sup>*1</sup>		$5.0 \times 10^6$ $2.0 \times 10^7$ (with function of linearity correction)			$\text{s}^{-1}$
Dark Count <sup>*2</sup>	Typ.	50	50	600	$\text{s}^{-1}$
	Max.	100	100	1000	$\text{s}^{-1}$
Pulse-pair Resolution		20			ns
Counter Gate Time		1 to 10 000 (PC Control)			ms
Counter Method		Double counter			—
Count Date		4 byte (MSB: Overlight Detection bit)			—
Interface		USB 2.0			—
Compatible OS		Windows 7 Pro/XP Pro/2000 (32 bit OS only)			—
Operating Ambient Temperature <sup>*3</sup>		+5 to +40			°C
Storage Temperature <sup>*3</sup>		-20 to +50			°C
Weight		54			g

\*1: Random pulse, at 10 % count loss.


\*2: After 30 minutes storage in darkness at plateau voltage.

\*3: No condensation


### Characteristics (Count sensitivity, Dark count)




#### Count Rate Linearity and Over Light Detection Output



#### Count Rate Linearity Correction




### Block Diagram




### Options

#### (Optical Fiber Adapter)(Unit: mm)

##### E5776 (FC Type)



##### E5776-51 (SMA Type)



### Dimensional Outlines (Unit: mm)

